

1. 庄司浩一（農業食料工学会編）：農業食料工学ハンドブック, 7 編 土と耕うん 4.1.1 モールドボードプラウ/4.1.2 ディスクプラウ(円板プラウ)/4.2.5 研究動向と性能評価/10 編 穀物の収穫 1.2.8 収量・成分測定装置. コロナ社, 1108 頁, 434-438/ 444/ 608-612, 2020.
2. 庄司浩一（農業食料工学会編）：ポストハーベスト工学事典, 5 加工 5.1 粃摺. 朝倉書店, 440 頁, 200-201, 2019.
3. 庄司浩一（伊藤一幸編著）：エシカルな農業, 第 1 部 4 有機水田には新しい機械除草を. 誠文堂新光社, 264 頁, 45-57, 2016.
4. 庄司浩一（中塚雅也編）：農村で学ぶはじめの一步, 7 田畑・水の管理と農作業/ 21 田畑・水の管理と農業機械の見方/【コラム】米の食味と非破壊測定技術. 昭和堂出版, 168 頁, 26-29/ 88-91/ 104-105, 2011.
5. 庄司浩一（池田義郎, 笈田昭, 梅田幹雄編）：農業機械学第 3 版, 第 4 章 耕うん・整地機械 2. プラウ. 文永堂出版, 298 頁, 108-116, 2006.

1. 庄司浩一*, 安達康弘: 水稻の不耕起移植における植溝形成が生育・収量に与える影響. 農作業研究, 60(4), 147-159, 2025,
2. Oyeboode O.[#], Andoniaina R. M., Iijima M., Shoji K.^{*}: Draft requirements of vertically oscillating tractor-mounted subsoiler. 農業食料工学会誌, 84(2), 110-112, 2022.
3. Oyeboode O.[#], Andoniaina R. M., Shoji K.^{*}: Draft reduction without increase in power requirement using a vertically oscillating model subsoiler. 農業食料工学会誌, 83(5), 361-368, 2021.
4. Oyeboode O.[#], Shoji K.^{*}: Development of a simple, movable, indoor soil bin equipped with some novel measuring and soil preparation devices. Arid Zone Journal of Engineering, Technology and Environment, 16(4), 751-762, 2020.
5. Andoniaina R. M.[#], Yakiyama H., Shoji K.^{*}: Arrayed rice mat seedlings for saving seeds – Focusing on missing hills and hill mortality –. 農業食料工学会誌, 82(5), 497-504, 2020.
6. Andoniaina R. M.[#], Shoji K.^{*}: Free-pivoting suspension on one-wheel two-row walk-behind rice transplanter. 農業食料工学会誌, 82(1), 57-64, 2020.
7. Hirooka Y.^注, Shoji K.^注, Watanabe Y., Izumi Y., Awala S. K. , Iijima M.: Ridge formation with strip tillage alleviates excess moisture stress for drought-tolerant crops. Soil and Tillage Research, 195, No. 104429 (8 pages), 2019. 注 These authors equally contributed to the research.
8. Andoniaina R. M.[#], Yakiyama H., Shoji K.^{*}: Thirty-row arrayed rice mat seedlings – Saving seeds and prolonging plant lifespan –. 農業食料工学会誌, 80(5), 320-321, 2018.
9. Pitoyo J.[#], Shoji K.^{*}, Kawamura T.: Weeding efficacy and power requirement of walking-type power weeder under varying rotor slippage in paddy field. 農業食料工学会誌, 79(3), 273-278, 2017.
10. Pitoyo J.[#], Shoji K.^{*}, Kawamura T.: Engine reaction torque sensing on walking-type power weeder. 農業食料工学会誌, 79(1), 74-79, 2017.
11. Shoji K.^{*}, Miyamoto M. Improving the accuracy of estimating grain weight by discriminating each grain impact on the yield sensor. Precision Agriculture, 15(1), 31-43, 2014.
12. Shoji K.^{*}, Itoh K., Kawahara F., Yoshida Y.[#], Yamamoto Y., Sudo K.: Micro-elevations in paddy field affect efficacy of mechanical weeding – A case study for evaluation of weeding machines for controlling *Monochoria vaginalis* in herbicide-free farming –, Weed Biology and Management, 13, 45-52, 2013.
13. Shoji K.^{*}, Arai K.[#], Ushio A., Kawamura T.: (Stafford J. V. ed.) Precision Agriculture '13, Microphone sensor for grain yield monitoring. Wageningen Academic Publisher, 824 pages, 57-62, 2013.
14. Marnadee C., Kawamura T., Shoji K.: Development of driving and steering unit of orchard sprinkler boat using fluidics- switching characteristics, bow thrust of the model fluidics and boat turning radius -, Engineering in Agriculture, Environment and Food, 5(4), 121-125, 2012.
15. Shoji K.^{*}, Yamaguchi D., Horio H.: Fine-crushing of wood-cellulosic material modified for its hydrolysis for bioethanol production. Engineering in Agriculture, Environment and Food, 4(3), 62-65, 2011.
16. Shoji K.^{*}, Matsumoto I., Kawamura T.: Impact-by-impact sensing of grain flow on *jidatsu* combine for enhanced accuracy of yield sensor. Engineering in Agriculture, Environment and Food, 4(1), 1-6, 2011.

17. Marnadee C., Horio H., Kawamura T., Shoji K.: Development of fluidics for driving and steering unit of orchard sprinkler boat – Switching characteristics of fluidics and bow thrust –. Engineering in Agriculture, Environment and Food, 3(1), 7-13, 2010.
18. Shoji K.*, Itoh H., Kawamura T.: In-situ non-linear calibration of grain-yield sensor – Optimization of parameters for flow rate of grain vs. force on the sensor –. Engineering in Agriculture, Environment and Food, 2(3), 78-82, 2009.
19. Shoji K.*, Itoh H., Kawamura T.: A mini- grain yield sensor compensating for the drift of its own output. Engineering in Agriculture, Environment and Food, 2(2), 44-48, 2009.
20. Yamaguchi D., Hatano A., Shoji K., Itoh H., Kawamura T., Horio H.: Fine-crushing and subcritical water treatment of wood materials suitable for bioethanol production using image processing as intermediate indicators. Biosystems Engineering, 101(4), 436-444, 2008.
21. 庄司浩一*, 山口雄司, 川村恒夫, 安藤和登: RTK-GPS を用いた圃場の高低差マップの精度評価. 農業機械学会誌, 70(5), 83-91, 2008.
22. Qarallah B.#, Shoji K.*, Kawamura T.: Development of yield sensor for measuring individual weights of onion bulbs. Biosystems Engineering, 100(4), 511-515, 2008.
23. 庄司浩一*, 小林伸哉, 堀尾尚志, 川村恒夫: 水稻栽培試験における収量計測コンバインを利用した収量比較法. 農作業研究, 42(2), 105-110, 2007.
24. Shoji K.*: Development of spot plow providing complete inversion for effective weed control. Weed Biology and Management, 7(1), 14-22, 2007.
25. Yamaguchi D., Shoji K., Kawamura T., Itoh H., Horio H.: Processing technology for ethanol production from wood-cellulosic materials (Part I) – Development of flail-knife fine-crusher for chopped wood materials –. 農業機械学会誌, 68(6), 91-100, 2006.
26. Shoji K.*, Kawamura T., Horio H., Nakayama K., Kobayashi N.: Variability of micro-elevation, yield, and protein content within a transplanted paddy field. Precision Agriculture, 6(1), 73-86, 2005.
27. Purwantana B., Horio H., Shoji K., Kawamura T.: Basic studies on frail-type rotary cultivator for swampy land preparation (Part 2) – Root-matted soil behavior under impact shear cutting –. 農業機械学会誌, 66(3), 84-90, 2004.
28. Shoji K.*: Forces on model ‘spot plough’. Biosystems Engineering, 87(1), 39-45, 2004.
29. Purwantana B., Horio H., Shoji K., Kawamura T.: Basic studies on frail-type rotary cultivator for swampy land preparation – Grass cutting characteristics and energy requirement –. 農業機械学会誌, 65(5), 76-83, 2003.
30. 庄司浩一*, 谷森文彦, 中山和明, 川村恒夫, 小林伸哉, 堀尾尚志: 水田内の高低差が収量および品質の変動に与える影響. 農作業研究, 38(2), 73-78, 2003.
31. Purwantana B., Horio H., Kawamura T., Shoji K.: Performance evaluation of a frail-type rotary cultivator for cutting grass in swampland. Agricultural Engineering Journal, 11(4), 207-217, 2002.
32. 川村恒夫, 庄司浩一, 徳田勝: 水稻の脱粒力の測定. 農業機械学会誌, 64(5), 116-122, 2002.
33. Shoji K.*, Kawamura T., Horio H.: Impact-based grain yield sensor with compensation for vibration and drift. 農業機械学会誌, 64(5), 108-115, 2002.

34. Shoji K. *: Design of a model 'spot plough' for inversion of soil slice within the furrow. Journal of Agricultural Engineering Research, 79(3), 283-297, 2001.
35. 庄司浩一, 川村恒夫, 堀尾尚志 : 移植田と散播田における水稻の収量マップの作成. 農業機械学会誌, 62(2), 167-174, 2000.
36. 庄司浩一, 川村恒夫 : 水稻の収量マップの作成. 農業機械学会誌, 60(4), 73-74, 1998.

1. 庄司浩一: 水を味方につける農作業: 気候変動を乗り越え安定生産に向けて. 農業および園芸, 96(1), 2-7, 2021.
2. Shoji K. *: Current status and potentials for the use of agricultural machines in rice production in Madagascar. Agricultural Mechanization in Asia, Africa and Latin America, 49(2), 46-53, 2018.
3. 伊藤一幸, 庄司浩一: 今後の稲作経営の安定化に向けた除草機や除草剤の考え方, 農業, 1611, 33-40, 2016.